

PREDICTED ENERGY ASSESSMENT


Plot 19, 9, School View,
Askam in Furness,
Cumbria,
LA16 7FN

Dwelling type: Bungalow, Semi-Detached
Date of assessment: 09/08/2023
Produced by: BREW Compliance Ltd
Total floor area: 69.29 m²

This document is a Predicted Energy Assessment for properties marketed when they are incomplete. It includes a predicted energy rating which might not represent the final energy rating of the property on completion. Once the property is completed, this rating will be updated and an official Energy Performance Certificate will be created for the property. This will include more detailed information about the energy performance of the completed property.

The energy performance has been assessed using the Government approved SAP2012 methodology and is rated in terms of the energy use per square meter of floor area; the energy efficiency is based on fuel costs and the environmental impact is based on carbon dioxide (CO₂) emissions.

Energy Efficiency Rating




England

EU Directive
2002/91/EC

The energy efficiency rating is a measure of the overall efficiency of a home. The higher the rating the more energy efficient the home is and the lower the fuel bills are likely to be.

Environmental Impact (CO₂) Rating



England

EU Directive
2002/91/EC

The environmental impact rating is a measure of a home's impact on the environment in terms of carbon dioxide (CO₂) emissions. The higher the rating the less impact it has on the environment.

This report has not been submitted through the Elmhurst Energy members' portal, therefore results are subject to change when the dwelling is completed.

BUILDING REGULATION COMPLIANCE

Calculation Type: New Build (As Designed)

Property Reference	Plot 19			Issued on Date	09/08/2023
Assessment Reference	As Built	Prop Type Ref	Bungalow		
Property	Plot 19, 9, School View, Askam in Furness, Cumbria, LA16 7FN				
SAP Rating	83 B	DER	18.96	TER	19.87
Environmental	86 B	% DER<TER	4.59		
CO ₂ Emissions (t/year)	1.23	DFEE	50.83	TFEE	55.06
General Requirements Compliance	Pass	% DFEE<TFEE	7.69		
Assessor Details	Mr. Kieran Abadie, BREW Compliance Ltd, Tel: 07943 063 981, kieran@brewcompliance.co.uk			Assessor ID	AX84-0001
Client	Moorsolve Limited, Moorsolve				

SUMMARY FOR INPUT DATA FOR New Build (As Designed)

Criterion 1 – Achieving the TER and TFEE rate

1a TER and DER

Fuel for main heating	Mains gas		
Fuel factor	1.00 (mains gas)		
Target Carbon Dioxide Emission Rate (TER)	19.87	kgCO ₂ /m ²	
Dwelling Carbon Dioxide Emission Rate (DER)	18.96	kgCO ₂ /m ²	Pass
	-0.91 (-4.6%)	kgCO ₂ /m ²	

1b TFEE and DFEE

Target Fabric Energy Efficiency (TFEE)	55.06	kWh/m ² /yr	
Dwelling Fabric Energy Efficiency (DFEE)	50.83	kWh/m ² /yr	
	-4.3 (-7.8%)	kWh/m ² /yr	Pass

Criterion 2 – Limits on design flexibility

Limiting Fabric Standards

2 Fabric U-values

Element	Average	Highest	
External wall	0.20 (max. 0.30)	0.20 (max. 0.70)	Pass
Party wall	0.00 (max. 0.20)	-	Pass
Floor	0.12 (max. 0.25)	0.12 (max. 0.70)	Pass
Roof	0.11 (max. 0.20)	0.11 (max. 0.35)	Pass
Openings	1.43 (max. 2.00)	1.44 (max. 3.30)	Pass

2a Thermal bridging

Thermal bridging calculated from linear thermal transmittances for each junction

3 Air permeability

Air permeability at 50 pascals	5.10 (design value)	m ³ /(h.m ²) @ 50 Pa	
Maximum	10.0	m ³ /(h.m ²) @ 50 Pa	Pass

Limiting System Efficiencies

4 Heating efficiency

This report has not been submitted through the Elmhurst Energy members' portal, therefore results are subject to change when the dwelling is completed.

BUILDING REGULATION COMPLIANCE

Calculation Type: New Build (As Designed)

Main heating system

Boiler system with radiators or underfloor - Mains gas
Data from database
Ideal LOGIC COMBI ESP1 30
Combi boiler
Efficiency: 89.6% SEDBUK2009
Minimum: 88.0%

Pass

Secondary heating system

None

5 Cylinder insulation

Hot water storage

No cylinder

6 Controls

Space heating controls

Time and temperature zone control

Pass

Hot water controls

No cylinder

Boiler interlock

Yes

Pass

7 Low energy lights

Percentage of fixed lights with low-energy fittings

100 %

Minimum

75 %

Pass

8 Mechanical ventilation

Not applicable

Criterion 3 – Limiting the effects of heat gains in summer

9 Summertime temperature

Overheating risk (North West England)

Not significant

Pass

Based on:

Overshading

Average

Windows facing North East

2.79 m², No overhang

Windows facing South East

0.73 m², No overhang

Windows facing South West

5.27 m², No overhang

Air change rate

8.00 ach

Blinds/curtains

None

Criterion 4 – Building performance consistent with DER and DFEE rate

Party Walls

Type

U-value

Filled Cavity with Edge Sealing

0.00

W/m²K

Pass

Air permeability and pressure testing

3 Air permeability

Air permeability at 50 pascals

5.10 (design value)

m³/(h.m²) @ 50 Pa

Maximum

10.0

m³/(h.m²) @ 50 Pa

Pass

10 Key features

Party wall U-value

0.00

W/m²K

Roof U-value

0.11

W/m²K

Floor U-value

0.12

W/m²K

This report has not been submitted through the Elmhurst Energy members' portal, therefore results are subject to change when the dwelling is completed.

THERMAL BRIDGING

Calculation Type: New Build (As Designed)

Property Reference	Plot 19	Issued on Date	09/08/2023
Assessment Reference	As Built	Prop Type Ref	Bungalow
Property	Plot 19, 9, School View, Askam in Furness, Cumbria, LA16 7FN		
SAP Rating	83 B	DER	18.96
Environmental	86 B	TER	19.87
CO ₂ Emissions (t/year)	1.23	% DER<TER	4.59
General Requirements Compliance	Pass	DFEE	50.83
		TFEE	55.06
		% DFEE<TFEE	7.69
Assessor Details	Mr. Kieran Abadie, BREW Compliance Ltd, Tel: 07943 063 981, kieran@brewcompliance.co.uk		Assessor ID
			AX84-0001
Client	Moorsolve Limited, Moorsolve		

	Junction detail	Source Type	Psi (W/mK)	Length (m)	Result	Reference
External wall	E2 Other lintels (including other steel lintels)	Table K1 - Approved	0.300	7.14	2.14	
External wall	E3 Sill	Table K1 - Approved	0.040	4.35	0.17	
External wall	E4 Jamb	Table K1 - Approved	0.050	17.52	0.88	
External wall	E5 Ground floor (normal)	Table K1 - Approved	0.160	25.79	4.13	
External wall	E10 Eaves (insulation at ceiling level)	Table K1 - Approved	0.060	14.40	0.86	
External wall	E12 Gable (insulation at ceiling level)	Table K1 - Approved	0.240	19.96	4.79	
External wall	E16 Corner (normal)	Table K1 - Approved	0.090	7.20	0.65	
External wall	E17 Corner (inverted – internal area greater than external area)	Table K1 - Approved	-0.090	2.40	-0.22	
External wall	E18 Party wall between dwellings	Table K1 - Approved	0.060	4.80	0.29	
Party wall	P1 Party wall - Ground floor	Table K1 - Default	0.160	8.57	1.37	
Party wall	P4 Party wall - Roof (insulation at ceiling level)	Table K1 - Default	0.240	8.57	2.06	

Total: **17.12** W/mK:
Y-Value: **0.085** W/m²K:

BASIC COMPLIANCE REPORT

Calculation Type: New Build (As Designed)

Property Reference	Plot 19	Issued on Date	09/08/2023
Assessment Reference	As Built	Prop Type Ref	Bungalow
Property	Plot 19, 9, School View, Askam in Furness, Cumbria, LA16 7FN		
SAP Rating	83 B	DER	18.96
Environmental	86 B	TER	19.87
CO ₂ Emissions (t/year)	1.23	% DER<TER	4.59
General Requirements Compliance	Pass	DfEE	50.83
		TfEE	55.06
		% DfEE<TfEE	7.69
Assessor Details	Mr. Kieran Abadie, BREW Compliance Ltd, Tel: 07943 063 981, kieran@brewcompliance.co.uk		Assessor ID
			AX84-0001
Client	Moorsolve Limited, Moorsolve		

SUMMARY FOR INPUT DATA FOR New Build (As Designed)

Criterion 1 – Achieving the TER and TfEE rate

1a TER and DER

Fuel for main heating	Mains gas		
Fuel factor	1.00 (mains gas)		
Target Carbon Dioxide Emission Rate (TER)	19.87	kgCO ₂ /m ²	
Dwelling Carbon Dioxide Emission Rate (DER)	18.96	kgCO ₂ /m ²	Pass
	-0.91 (-4.6%)	kgCO ₂ /m ²	

1b TfEE and DfEE

Target Fabric Energy Efficiency (TfEE)	55.06	kWh/m ² /yr	
Dwelling Fabric Energy Efficiency (DfEE)	50.83	kWh/m ² /yr	
	-4.3 (-7.8%)	kWh/m ² /yr	Pass

Criterion 2 – Limits on design flexibility

Limiting Fabric Standards

2 Fabric U-values

Element	Average	Highest	
External wall	0.20 (max. 0.30)	0.20 (max. 0.70)	Pass
Party wall	0.00 (max. 0.20)	-	Pass
Floor	0.12 (max. 0.25)	0.12 (max. 0.70)	Pass
Roof	0.11 (max. 0.20)	0.11 (max. 0.35)	Pass
Openings	1.43 (max. 2.00)	1.44 (max. 3.30)	Pass

2a Thermal bridging

Thermal bridging calculated from linear thermal transmittances for each junction

3 Air permeability

Air permeability at 50 pascals	5.10 (design value)	
Maximum	10.0	Pass

Limiting System Efficiencies

4 Heating efficiency

BASIC COMPLIANCE REPORT

Calculation Type: New Build (As Designed)

Main heating system

Boiler system with radiators or underfloor - Mains gas
Data from database
Ideal LOGIC COMBI ESP1 30
Combi boiler
Efficiency: 89.6% SEDBUK2009
Minimum: 88.0%

Pass

Secondary heating system

None

5 Cylinder insulation

Hot water storage

No cylinder

6 Controls

Space heating controls

Time and temperature zone control

Pass

Hot water controls

No cylinder

Boiler interlock

Yes

Pass

7 Low energy lights

Percentage of fixed lights with low-energy fittings

100

%

Minimum

75

%

Pass

8 Mechanical ventilation

Not applicable

Criterion 3 – Limiting the effects of heat gains in summer

9 Summertime temperature

Overheating risk (North West England)

Not significant

Pass

Based on:

Overshading

Average

Windows facing North East

2.79 m², No overhang

Windows facing South East

0.73 m², No overhang

Windows facing South West

5.27 m², No overhang

Air change rate

8.00 ach

Blinds/curtains

None

Criterion 4 – Building performance consistent with DER and DFEE rate

Party Walls

Type

U-value

Filled Cavity with Edge Sealing

0.00

W/m²K

Pass

Air permeability and pressure testing

3 Air permeability

Air permeability at 50 pascals

5.10 (design value)

Maximum

10.0

Pass

10 Key features

Party wall U-value

0.00

W/m²K

Roof U-value

0.11

W/m²K

Floor U-value

0.12

W/m²K

This report has not been submitted through the Elmhurst Energy members' portal, therefore results are subject to change when the dwelling is completed.

SUMMARY FOR INPUT DATA

Calculation Type: New Build (As Designed)

Property Reference	Plot 19	Issued on Date	09/08/2023
Assessment Reference	As Built	Prop Type Ref	Bungalow
Property	Plot 19, 9, School View, Askam in Furness, Cumbria, LA16 7FN		
SAP Rating	83 B	DER	18.96
Environmental	86 B	TER	19.87
CO ₂ Emissions (t/year)	1.23	% DER<TER	4.59
General Requirements Compliance	Pass	DfEE	50.83
		TFEE	55.06
		% DfEE<TFEE	7.69
Assessor Details	Mr. Kieran Abadie, BREW Compliance Ltd, Tel: 07943 063 981, kieran@brewcompliance.co.uk		Assessor ID
			AX84-0001
Client	Moorsolve Limited, Moorsolve		

SUMMARY FOR INPUT DATA FOR: New Build (As Designed)

Orientation	North East
Property Tenure	Owner-occupied
Transaction Type	New dwelling
Terrain Type	Suburban
1.0 Property Type	Bungalow, Semi-Detached
2.0 Number of Storeys	1
3.0 Date Built	2023
4.0 Sheltered Sides	2
5.0 Sunlight/Shade	Average or unknown

6.0 Measurements	Heat Loss Perimeter	Internal Floor Area	Average Storey Height
	Ground Floor: 25.79 m	69.29 m ²	2.40 m

7.0 Living Area	17.55	m ²
-----------------	-------	----------------

8.0 Thermal Mass Parameter	Simple calculation - Low	
Thermal Mass	100.00	kJ/m²K

9.0 External Walls		U-Value (W/m ² K)	Gross Area (m ²)	Nett Area (m ²)
Description	Type			
External Wall	Timber Frame	0.20	61.91	51.06

9.1 Party Walls		U-Value (W/m ² K)	Area (m ²)
Description	Type		
Party Wall	Filled Cavity with Edge Sealing	0.00	20.56

10.0 External Roofs		U-Value (W/m ² K)	Gross Area (m ²)	Nett Area (m ²)
Description	Type			
External Roof	External Plane Roof	0.11	69.29	69.29

11.0 Heat Loss Floors		U-Value (W/m ² K)	Area (m ²)
Description	Type		
Ground Floor	Ground Floor - Solid	0.12	69.29

12.0 Opening Types

SUMMARY FOR INPUT DATA

Calculation Type: New Build (As Designed)

Description	Data Source	Type	Glazing	Glazing Gap	Argon Filled	G-value	Frame Type	Frame Factor	U Value (W/m²K)
Glazing	Manufacturer	Window	Double Low-E Soft 0.05			0.63		0.70	1.44
Doors	Manufacturer	Solid Door							1.40
1/2 Doors	Manufacturer	Half Glazed Door	Double Low-E Soft 0.05			0.63		0.70	1.40

13.0 Openings

Name	Opening Type	Location	Orientation	Curtain Type	Overhang Ratio	Wide Overhang	Width (m)	Height (m)	Count	Area (m²)	Curtain Closed
Front	Window	[1] External Wall	North East	None	0.00					2.79	
Rear	Window	[1] External Wall	South West	None	0.00					5.27	
Entrance	Solid Door	[1] External Wall	North East							2.06	
Side	Window	[1] External Wall	South East	None	0.00					0.73	

14.0 Conservatory

None

15.0 Draught Proofing

100

%

16.0 Draught Lobby

No

17.0 Thermal Bridging

Calculate Bridges

17.1 List of Bridges

Source Type	Bridge Type	Length	Psi	Imported
Table K1 - Approved	E2 Other lintels (including other steel lintels)	7.14	0.300	No
Table K1 - Approved	E3 Sill	4.35	0.040	No
Table K1 - Approved	E4 Jamb	17.52	0.050	No
Table K1 - Approved	E5 Ground floor (normal)	25.79	0.160	No
Table K1 - Approved	E10 Eaves (insulation at ceiling level)	14.40	0.060	No
Table K1 - Approved	E12 Gable (insulation at ceiling level)	19.96	0.240	No
Table K1 - Approved	E16 Corner (normal)	7.20	0.090	No
Table K1 - Approved	E17 Corner (inverted – internal area greater than external area)	2.40	-0.090	No
Table K1 - Approved	E18 Party wall between dwellings	4.80	0.060	No
Table K1 - Default	P1 Party wall - Ground floor	8.57	0.160	No
Table K1 - Default	P4 Party wall - Roof (insulation at ceiling level)	8.57	0.240	No

Y-value	0.085	W/m²K
---------	-------	-------

18.0 Pressure Testing

Yes

Designed AP ₅₀	5.10	m³/(h.m²) @ 50 Pa
---------------------------	------	-------------------

Property Tested ?		
-------------------	--	--

As Built AP ₅₀		m³/(h.m²) @ 50 Pa
---------------------------	--	-------------------

19.0 Mechanical Ventilation

Summer Overheating

Windows open in hot weather Windows fully open

Cross ventilation possible Yes

Night Ventilation No

Air change rate 8.00

Mechanical Ventilation

Mechanical Ventilation System Present No

20.0 Fans, Open Fireplaces, Flues

	MHS	SHS	Other	Total
Number of Chimneys	0		0	0
Number of open flues	0		0	0
Number of intermittent fans				2
Number of passive vents				0

SUMMARY FOR INPUT DATA

Calculation Type: New Build (As Designed)

Number of flueless gas fires 0

21.0 Fixed Cooling System No

22.0 Lighting

Internal

Total number of light fittings 10
Total number of L.E.L. fittings 10
Percentage of L.E.L. fittings 100.00 %

External

External lights fitted No

23.0 Electricity Tariff Standard

24.0 Main Heating 1

Database
Description Combination Boiler
Percentage of Heat 100 %
Database Ref. No. 17956
Fuel Type Mains gas
Main Heating BGW
SAP Code 104
In Winter 90.5
In Summer 87.3
Controls CBI Time and temperature zone control
PCDF Controls 0
Delayed Start Stat No
Sap Code 2110
Flue Type Balanced
Fan Assisted Flue Yes
Is MHS Pumped Pump in heated space
Heat Emitter Radiators
Flow Temperature Normal (> 45°C)
Combi boiler type Standard Combi
Combi keep hot type None

25.0 Main Heating 2 None

Community Heating None

28.0 Water Heating

HWP From main heating 1
Water Heating Main Heating 1
Flue Gas Heat Recovery System No
Waste Water Heat Recovery Instantaneous System 1 No
Waste Water Heat Recovery Instantaneous System 2 No
Waste Water Heat Recovery Storage System No
Solar Panel No
Water use <= 125 litres/person/day Yes
SAP Code 901

SUMMARY FOR INPUT DATA

Calculation Type: New Build (As Designed)

29.0 Hot Water Cylinder

None

Recommendations

Lower cost measures

None

Further measures to achieve even higher standards

	Typical Cost	Typical savings per year	Ratings after improvement	
			SAP rating	Environmental Impact
Solar water heating	£4,000 - £6,000	£76	B 84	
	Typical Cost	Typical savings per year	Ratings after improvement	
			SAP rating	Environmental Impact
Solar photovoltaic panels, 2.5 kWp	£3,500 - £5,500	£679	A 96	